

Adresy MAC interfejsów sieciowych w komputerach lab204

PC	pierwszy interfejs ethernetowy (zintegrowany na płycie głównej zwykle eth0)	drugi interfejs ethernetowy (karta PCI ze złączem BNC zwykle eth1)
1	00:0c:6e:6b:61:bf	00:48:45:00:40:13
2	00:0c:6e:6b:61:e4	00:48:45:00:3f:2d
3	00:0c:6e:6b:27:a5	00:48:45:00:44:7e
4	00:0c:6e:6b:25:96	00:48:45:00:41:29
5	00:0c:6e:6b:5e:ee	00:48:45:00:40:45
6	00:0c:6e:6b:62:3e	00:48:45:00:45:30
7	00:0c:6e:6b:61:92	00:48:45:00:43:68
8	00:0c:6e:6b:62:28	00:48:45:00:3b:1f
9	00:0c:6e:6b:61:b1	00:48:45:00:40:5d
10	00:0c:6e:6b:61:90	00:48:45:00:45:97
11	00:0c:6e:6b:61:dc	00:48:45:00:45:aa
12	00:0c:6e:6b:26:f0	00:48:45:00:41:33
13	00:0c:6e:6b:5f:13	00:48:45:00:41:39
14	00:0c:6e:6b:5e:d5	00:48:45:00:41:da
15	00:0b:6a:56:8f:ce	00:00:e8:64:92:7b
16	00:50:8d:51:07:ce	00:30:4f:08:e1:66
17	00:50:8d:51:84:0d	00:48:45:00:44:20
18	00:50:8d:51:95:71	00:48:45:00:43:7a